

Without measurement there is no control®

AirSentry® II

Mobile AMC Detection System



Mobile system with parts-per-trillion sensitivity and fast response times

Designed to enhance fixed AMC monitoring programs, the AirSentry® II Mobile AMC Detection System is the first truly mobile system for monitoring airborne molecular contamination in cleanrooms. Mobility plays an important part in a strategic AMC monitoring program, allowing contamination sources to be quickly located, quantified and eliminated.

A local touch PC on the mobile cart provides instant feedback of AMC levels at each monitoring location. FacilityNet™ software provides data storage and graphical displays in real-time while monitoring the specific environment.

Onboard, chemically filtered, clean dry air (CDA) and vacuum are supplied within the cart enclosure to ensure that the analyzers can sample immediately upon relocation without long analyzer warm-up times incurred by competitive systems.

BENEFITS

- Pinpoint AMC issues in real-time, by identifying contamination sources
- Characterize AMC levels in multiple areas of large cleanrooms
- AMC analyzers available where and when needed, to deploy anytime
- Continuous actionable data in the process tool and facility

FEATURES

- High-sensitivity AirSentry II ion mobility spectrometry (IMS) analyzers detect acids, amines, ammonia and chlorides
- Mobile cart – move the system quickly to high-priority sample locations
- Onboard compressor, air-dryer, chemical filter and vacuum pump
- Battery back-up enables uninterrupted sampling, even during transport
- Touch PC and software display real-time and historical concentration data
- Optional wireless data communication

APPLICATIONS

- Troubleshooting and spatial identification of contamination sources
- Isolation and verification of AMC events detected by multi-point monitoring systems
- Testing of AMC levels within minienvironments and process tools
- Testing and validation of chemical filtration performance

AirSentry® II Mobile AMC Detection System

PARAMETER	SPECIFICATION	
Cart size (H x W x L)	49.6 x 25.6 x 39.4 in (126.0 x 65 x 100.0 cm)	
Weight	< 340 lb (154 kg)	
Analytical wetted surfaces	Teflon™, electropolished 316 stainless steel	
CDA quality*	< - 60 °C dew point, chemically filtered	
CDA capacity*	> 800 cc/min for < 30 minutes	
Working time (fully-charged/pressurized)	30 minutes, under optimal conditions	
Bypass CDA inlet (low vibration mode)	1/4" Swagelok®	
Vacuum	25 kPa (absolute), 1,500 cc/min	
Available analyzers (LDL - Lower Detection Limit 3 σ)	AirSentry II Acids, 0 – 50 ppb _v AirSentry II Amines, 0 – 50 ppb _v AirSentry II Ammonia, 0 – 50 ppb _v AirSentry II Chlorides, 0 – 50 ppb _v	LDL = 0.2 ppb _v LDL = 0.2 ppb _v LDL = 0.2 ppb _v LDL = 0.5 ppb _v
Temperature range	59 – 82 °F (15 – 28 °C)	
Operating storage	- 40 – + 122 °F (- 40 – + 50 °C)	
Humidity range	30 – 50% RH	
Operating storage	0 – 90% RH	
Communication and data transfer	Ethernet , USB	
Software	FacilityNet™ and AirSentry II Service Software	
Operating system	Microsoft Windows® 7	
Utility requirements:	115 VAC, 60 Hz	
User-supplied power (single phase)	230 VAC, 50 Hz	
CE-Declaration of Conformity	CE-certified	

* CDA quality and capacity are also required on an external CDA supply line, when the cart is used in low-vibration mode.

NEED MORE INFORMATION? Scan the QR code to connect with our team for guidance



HEADQUARTERS

7477 E. Dry Creek Parkway,
Niwot, CO, 80503 USA
T: +1 303 443 7100

Instrument Service & Support

T: +1 303-443-7100 ext.447

Service and Calibration

E: workorders@pmeasuring.com

Technical Support

E: techsupport@pmeasuring.com

Software or System Support

E: ssupport@pmeasuring.com

Customer Service and Order Processing

E: customerorders@pmeasuring.com

GLOBAL OFFICES

AUSTRIA

T: +43 171 728 285

E: pmsaustria@pmeasuring.com

BELGIUM/BENELUX

T: +32 10 23 71 56

E: pmsbelgium@pmeasuring.com

BRAZIL

T: +55 11 5188 8227

E: pmsbrazil@pmeasuring.com

CHINA

T: +86 400 081 8020

E: pmschina@pmeasuring.com

FRANCE

T: +33 682 991 798

E: pmsfrance@pmeasuring.com

GERMANY

T: +49 351 8896 3850

E: pmsgermany@pmeasuring.com

IRELAND

T: + 353 1 295 7373

E: Info.ie@pmeasuring.com

ITALY

T: +39 06 9053 0130

E: pmsrli@pmeasuring.com

JAPAN

T: +81 44 589 3498

E: pmsjapan@pmeasuring.com

KOREA

T: +82 31 286 5790

E: pmskorea@pmeasuring.com

NORDIC

T: +45 7070 2855

E: pmsnordic@pmeasuring.com

PUERTO RICO

T: +1 786 564 3356

E: pmspuertorico@pmeasuring.com

SINGAPORE

T: +65 6496 0342

E: pmssingapore@pmeasuring.com

SWITZERLAND

T: +41 71 987 01 01

E: pmsswitzerland@pmeasuring.com

TAIWAN

T: 886-3-5525300

E: pmstaiwan@pmeasuring.com

UNITED KINGDOM

T: +44 (0)1733 454 207

E: Info.uk@pmeasuring.com



AirSentry® is a registered trademark of Particle Measuring Systems, Inc. Windows® is a registered trademark of Microsoft Corporation. Teflon® is a registered trademark of The Chemours Company FC, LLC. Swagelok® is a registered trademark of Swagelok Company. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. © 2026 Particle Measuring Systems, Inc. All rights reserved. 05202026