

# HSLIS M65 ANSI/ISA-Compatible

Liquid Particle Counter



## BENEFITS

- Packaged for easy installation into Class I, Div II environments
- Particle measurement for solvents, chemicals and ultrapure water
- Simplify data analysis by using the same sensor throughout all of your fabs
- Low initial capital investment because packaging has already been completed
- Sealed package protects sensor from accidental chemical spills
- Simplified data interpretation and out-of-tolerance alerts with Facility Net

## FEATURES

- 0.065  $\mu\text{m}$  sizing sensitivity
- 4-20 mA outputs
- Sealed enclosure
- Fiberglass enclosure for chemical durability

## APPLICATIONS

- Class I, Div 2 environments
- Qualifying particle concentrations in a variety of acids, bases and mixtures
- Chemical delivery system monitoring
- In-line measurements in recirculating baths
- Quality assurance
- Continuous monitoring for process improvement

HSLIS M65 ANSI/ISA-compatible particle counters allow continuous real-time monitoring of fluid particle contamination levels in Class I, Div 2 environments.

Easily integrates into Facility Net software (or existing SCADA system) to provide an economical way to monitor multiple flow systems.

# HSLIS M65 ANSI/ISA-Compatible

Liquid Particle Counter

Specifications

Size range	0.065 - 0.2 µm
Channels	4
Channel sizes	0.065, 0.1, 0.15, 0.2 µm
Optimum flow rate (ml/min)	100 ± 10% ml/min
Sample volume	0.6 ml/min
Counting efficiency	100% of the sample volume
Maximum concentration <sup>1</sup>	10,000 counts/ml
Sample temperature	167 °F (75 °C)
Zero count level	< 2,000 counts/l
Wetted surface materials	Teflon®, Kel-F®, Sapphire and Kalraz® 4079
Dimensions (l, w, h)	19 x 13 x 9 in (48 x 33 x 23 cm)
Weight	22 lb (10 kg)
Power	100 - 240 VAC, 50 - 60 Hz, 1.0 Amp max.
Laser classification	Class 1, complies with US 21 CFR 1040.10 and EN 60825-1. Internally an enclosed Class 3B laser is used per EN 60825-1.
Calibration	Calibration materials used are traceable to the US NIST (National Institute of Standards and Technology)
Environment	Temperature: 50 - 90 °F (10 - 32 °C) Humidity: non-condensing
Communications	Ethernet: includes five (5) 4-20 mA outputs, four (4) particle channels, one (1) instrument status RS-232: one (1) input for set-up and diagnostics only

<sup>1</sup> Greater than 90% accuracy (less than 10% coincidence loss) at maximum recommended concentration.

All trademarks are the property of their respective owners.  
Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

## HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support  
T: +1 800 557 6363

Customer Response Center  
T: +1 877 475 3317  
E: [info@pmeasuring.com](mailto:info@pmeasuring.com)

[www.pmeasuring.com](http://www.pmeasuring.com)  
[info@pmeasuring.com](mailto:info@pmeasuring.com)



**PARTICLE  
MEASURING  
SYSTEMS®**  
a spectris company

## GLOBAL OFFICES

AUSTRIA  
T: +43 512 390 500  
E: [pmsaustria@pmeasuring.com](mailto:pmsaustria@pmeasuring.com)

BENELUX  
T: +32 10 23 71 56  
E: [pmsbelgium@pmeasuring.com](mailto:pmsbelgium@pmeasuring.com)

BRAZIL  
T: +55 11 5188 8227  
E: [pmsbrazil@pmeasuring.com](mailto:pmsbrazil@pmeasuring.com)

CHINA  
T: +86 21 6113 3600  
E: [pmschina@pmeasuring.com](mailto:pmschina@pmeasuring.com)

FRANCE  
T: 33(0)1 60 10 32 96  
E: [pmsfrance@pmeasuring.com](mailto:pmsfrance@pmeasuring.com)

GERMANY  
T: +49 6151 6671 632  
E: [pmsgermany@pmeasuring.com](mailto:pmsgermany@pmeasuring.com)

ITALY  
T: +39 06 9053 0130  
E: [pmsrl@pmeasuring.com](mailto:pmsrl@pmeasuring.com)

JAPAN  
T: +81 3 5298 8175  
E: [pmsjapan@pmeasuring.com](mailto:pmsjapan@pmeasuring.com)

KOREA  
T: +82 31 286 5790  
E: [pmskorea@pmeasuring.com](mailto:pmskorea@pmeasuring.com)

MEXICO  
T: +52 55 2271 5106  
E: [pmsmexico@pmeasuring.com](mailto:pmsmexico@pmeasuring.com)

NORDIC  
T: +45 707 028 55  
E: [pmsnordic@pmeasuring.com](mailto:pmsnordic@pmeasuring.com)

PUERTO RICO  
T: +1 787 718 9096  
E: [pmspuertorico@pmeasuring.com](mailto:pmspuertorico@pmeasuring.com)

SINGAPORE  
T: +65 6496 0330  
E: [pmsingapore@pmeasuring.com](mailto:pmsingapore@pmeasuring.com)

SWITZERLAND  
T: +41 71 987 01 01  
E: [pmsswitzerland@pmeasuring.com](mailto:pmsswitzerland@pmeasuring.com)

TAIWAN  
T: 886-3-5525300 Ext: 301  
E: [pms taiwan@pmeasuring.com](mailto:pms taiwan@pmeasuring.com)