

The Particle Measuring Systems®
Particle Sensor Safety Cabinet provides
chemical containment and safe operating
conditions for the Chem 20™ and
UltraChem® 40 or 100 chemical particle
counting sensors. The cabinet is designed
to sit on a shelf or other flat surface.

The cabinet enclosure houses the chemical particle sensor, detects chemical leaks with an external alarm, and provides secondary containment when a leak occurs. In the event of a chemical leak within the chemical particle counter or sample connections, the system will automatically detect the leak, shut off inlet and outlet sample valves, turn off power to the particle sensor, and provide an external alarm contact.

BENEFITS

- Provides safe containment of the chemical particle sensor
- Auto detection of chemical leak with alarms
- Enables safety shut-off of chemical sample lines during alarm conditions

FEATURES

- Secondary containment, polypropylene construction
- Intended for sampling of ambient temperature process chemicals between 15 to 40 °C
- Liquid leak detector
- · Safety cut-off switch
- External leak alarm light with external contact closure allows leak alarm communication to external systems
- Inlet and outlet sample shut-off valves
- PFA Bubble Separator to remove large bubbles
- Clear top access door with door interlock
- · Controlled power supply to the chemical particle counter
- Two pairs of side-mounted handles

APPLICATIONS

Particle monitoring of:

- Chemical distribution systems
- Semiconductor process tools
- High-purity chemical packaging plants



Particle Sensor Safety Cabinet

Acid/Base/Oxidizer Applications

Specifications

Cabinet Materials of Construction	Polypropylene
Sample Temperature	15 – 40 °C (59 – 104 °F)
Power	120 to 240 VAC, 50 – 60 Hz, 6 A
Sample Inlet Tubes	1/4-inch PFA, inlet and outlet
Sample Tube Outer Containment	3/4-inch FNPT, inlet and outlet
Exhaust	30 – 50 CFM, 2-inch threaded female connection
Drain Connection (in case of leak)	1/2-inch FNPT
Clean Dry Air	> 5 CFM, 30 PSI, 3/8-inch FNPT
Environment	15 – 30 °C (59 – 86 °F), Humidity < 60%, non-condensing
Alarm Indicator	Dome Light (G/R), external alarm connection available
External Dimensions (L x W x H)	39 x 28 x 15 in (99 x 71 x 38 cm)

HEADQUARTERS

5475 Airport Blvd Boulder, Colorado 80301 USA T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support T: +1 800 557 6363

Customer Response Center T: +1 877 475 3317 E: info@pmeasuring.com

www.pmeasuring.com info@pmeasuring.com



GLOBAL OFFICES

AUSTRIA

T: +43 512 390 500

E: pmsaustria@pmeasuring.com

BENELUX

T: +32 10 23 71 56

E: pmsbelgium@pmeasuring.com

BRAZIL

T: +55 11 5188 8227

E: pmsbrazil@pmeasuring.com

CHINA

T: +86 21 6113 3600

E: pmschina@pmeasuring.com

FRANCE

T: 33(0)1 60 10 32 96

E: pmsfrance@pmeasuring.com

ERMANY

T: +49 6151 6671 632

E: pmsgermany@pmeasuring.com

ΙΤΔΙΥ

T: +39 06 9053 0130

E: pmssrl@pmeasuring.com

JAPAN

T: +81 3 5298 8175

E: pmsjapan@pmeasuring.com

KOREA

T: +82 31 286 5790

E: pmskorea@pmeasuring.com

MEXICO

T: +52 55 2271 5106

E: pmsmexico@pmeasuring.com

ORDIC

T: +45 707 028 55

E: pmsnordic@pmeasuring.com

PUERTO RICO

T: +1 787 718 9096

E: pmspuertorico@pmeasuring.com

SINGAPORE

T: +65 6496 0330

E: pmssingapore@pmeasuring.com

SWITZERLAND

T: +41 71 987 01 01

E: pmsswitzerland@pmeasuring.com

ΤΔΙΜ/ΔΝ

T: 886-3-5525300 Ext: 301

E: pmstaiwan@pmeasuring.com