

Particle Sensor Safety Cabinet

Ambient Temperature Applications



The Particle Measuring Systems® Particle Sensor Safety Cabinet provides chemical containment and safe operating conditions for the Chem 20™ and UltraChem® 40 or 100 chemical particle counting sensors. The cabinet is designed to sit on a shelf or other flat surface.

The cabinet enclosure houses the chemical particle sensor, detects chemical leaks with an external alarm, and provides secondary containment when a leak occurs. In the event of a chemical leak within the chemical particle counter or sample connections, the system will automatically detect the leak, shut off inlet and outlet sample valves, turn off power to the particle sensor, and provide an external alarm contact.

BENEFITS

- Provides safe containment of the chemical particle sensor
- Auto detection of chemical leak with alarms
- Enables safety shut-off of chemical sample lines during alarm conditions

FEATURES

- Secondary containment, polypropylene construction
- Intended for sampling of ambient temperature process chemicals between 15 to 40 °C
- Liquid leak detector
- Safety cut-off switch
- External leak alarm light with external contact closure allows leak alarm communication to external systems
- Inlet and outlet sample shut-off valves
- PFA Bubble Separator to remove large bubbles
- Clear top access door with door interlock
- Controlled power supply to the chemical particle counter
- Two pairs of side-mounted handles

APPLICATIONS

Particle monitoring of:

- Chemical distribution systems
- Semiconductor process tools
- High-purity chemical packaging plants



Without measurement there is no control

Particle Sensor Safety Cabinet

Ambient Temperature Applications

Specifications

Cabinet Materials of Construction	Polypropylene
Sample Temperature	15 – 40 °C (59 – 104 °F)
Power	100 to 240 VAC, 50 – 60 Hz, 3 A
Sample Inlet Tubes	¼" PFA, inlet and outlet
Sample Tube Outer Containment	¾-inch FNPT, inlet and outlet
Exhaust	30 – 50 cfm, 2-inch threaded female connection
Drain Connection (in case of leak)	½-inch FNPT
Clean Dry Air	> 5 cfm, 30 psi, ½-inch FNPT
Environment	18 – 28 °C (64 – 82 °F), Humidity < 60%, non-condensing
Alarm Indicator	Dome Light (G/R), external alarm connection available
External Dimensions (L x W x H)	39 x 28 x 15 in (99 x 71 x 38 cm)



**PARTICLE
MEASURING
SYSTEMS®**

© 2017 Particle Measuring Systems, Inc. All rights reserved.
Chem 20™ is a trademark of Particle Measuring Systems, Inc.
UltraChem® is a registered trademark of Particle Measuring Systems, Inc.
All trademarks are the property of their respective owners.
Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

HEADQUARTERS

5475 Airport Blvd
Boulder, Colorado 80301 USA
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support
T: +1 800 557 6363

Customer Response Center
T: +1 877 475 3317
E: info@pmeasuring.com

GLOBAL OFFICES

AUSTRIA
T: +43 1 71 728 285
E: pmsaustria@pmeasuring.com

BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 21 6113 3600
E: pmschina@pmeasuring.com

FRANCE
T: +33 (0)1 60 10 32 96
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 6151 6671 632
E: pmsgermany@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmsrl@pmeasuring.com

JAPAN
T: +81 3 5298 8175
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

MEXICO
T: +52 55 2271 5106
E: pmsmexico@pmeasuring.com

NORDIC
T: +45 707 028 55
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 787 718 9096
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0330
E: pmssingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300 Ext: 301
E: pmstaiwan@pmeasuring.com